

Mipa Aceton is a quickly evaporating solvent for cleaning and degreasing of metal parts. It dissolves neoprene, adhesive residues and sticks polystyrene and acryl glass.  
Mipa Aceton can also be used as a dilution of synthetic resins and nitro-/nitro-combination paints.

Colour shade	colourless			
Mixing ratio	Apply with a brush or rag. After a short exposure time (max. 5 minutes) clean it with a clean cloth.			
Hardener	---			
Thinner	---			
Viscosity 20° C	---			
Application	spraying pressure	spraying nozzle	spraying operations	
Air / Flow jar				
Airless / Airmix				
Pot life	---			
Coat thickness / dry film	---			
Cure time	---			
Drying	recoat time	dust dry	set to touch	full hardeness
Object temp. 20° C				
Object temp. 60° C				

**Remarks:**

Keep containers tightly closed. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Provide adequate ventilation.

All products should be disposed of in relation to the regulations of the environmental health authorities. Protect your environment!

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.