

# Mipa Universal-Prefilled-Spray HPHC High Pressure High Coverage

Item no 21200 0016S  
Technical data sheet



page 1 / 2

## Intended use

Mipa Universal-Prefilled-Spray HPHC (HP = High Pressure / HC = High Coverage) is an aerosol for 400 ml. Universal pre-filled can with a mixture of propellant and solvent, which ensures high atomisation pressure and high hiding power. Suitable for all usual 1K paint systems based on synthetic resins, nitro-cellulose and acrylics. Mipa Universal-Prefilled-Spray HPHC can be filled individually. The technical paint properties correspond to those of the paint filled in. The specialist dealer (seller) is liable for the final product!

## Processing instructions



### Substrates

Depends on the product, see processing instructions of the paint filled in.

### Pre-treatment / cleansing

Depends on the product, see processing instructions of the paint filled in.

### Characteristics

Paint system is filled in the spray can by means of a filling machine  
Equipped with an adjustable sprayhead for fine atomisation  
Versatile use  
Suitable for use in combination with the Vario spray head

## Colour / gloss level

depends on the product, see processing instructions of the paint filled in.



### Preparation

Fill Mipa Universal-Prefilled-Spray with 100 ml of basic paint of the selected paint quality




After filling and before use, shake can vigorously for 1 - 2 min!



### Application

depends on the product, see processing instructions of the paint filled in.



### Flash-off time

depends on the product, see processing instructions of the paint filled in.



### After use

After use, turn can upside down and spray until the valve is clean, this prevents the valve from clogging up.


Version: en 0322

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

MIPA SE · Am Oberen Moos 1 · D-84051 Essenbach · Tel.: +49(0)87 03/922-0 · Fax: +49(0)87 03/922-100 · mipa@mipa-paints.com · www.mipa-paints.com

# Mipa Universal-Prefilled-Spray HPHC High Pressure High Coverage

Item no 21200 0016S  
Technical data sheet



## Drying time at 20 °C

depends on the product, see processing instructions of the paint filled in

**Processing conditions** depends on the product, see processing instructions of the paint filled in.

**Storage** Can be stored for 2 years in cool and dry places.

**VOC-regulation** EU limit value for the product (cat. B/e): 840 g/l  
This product contains max. 840 g/l of VOC.

**Safety information** See safety data sheet