

Mipa WBS Prefilled-Spray

Item no 21204 0000

Technical data sheet

mipa

Professional Coating Systems

page 1 / 2

Intended use

Mipa WBS Prefilled-Spray is especially suitable for the filling of water-based paints. Pre-filled with a mixture of propellant and other special additives. Suitable for Mipa WBC 2-Schicht-Basislacke and many other waterborne paint systems. Mipa WBS Prefilled-Spray can be filled individually. The technical paint properties correspond to those of the paint filled in. The specialist dealer (seller) is liable for the final product!

Processing instructions



Substrates

Depends on the product, see processing instructions of the paint filled in

For filling with Mipa WBC 2-Schicht-Basislack:

Well dried Mipa 1K and 2K primer / filler (in case of 1K systems, they must be overcoatable with water-based topcoats)
Cured and slightly sanded old paintworks; Carry out a test coating, if necessary!

Pre-treatment / cleansing


Depends on the product, see processing instructions of the paint filled in.

Characteristics

Paint system is filled in the spray can by means of a filling machine
Equipped with an adjustable sprayhead for fine atomisation
Versatile use

Colour / gloss level

depends on the product, see processing instructions of the paint filled in.



Preparation

Fill Mipa WBS Prefilled-Spray with 100 ml of basic paint of the selected paint quality

After filling and before use, shake can vigorously for 1 - 2 min!

Application

depends on the product, see processing instructions of the paint filled in.

Flash-off time

depends on the product, see processing instructions of the paint filled in.

Version: en 0322

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

MIPA SE · Am Oberen Moos 1 · D-84051 Essenbach · Tel.: +49(0)87 03/922-0 · Fax: +49(0)87 03/922-100 · mipa@mipa-paints.com · www.mipa-paints.com



After use

After use, turn can upside down and spray until the valve is clean, this prevents the valve from clogging up.



Drying time at 20 °C

depends on the product, see processing instructions of the paint filled in

Processing conditions

depends on the product, see processing instructions of the paint filled i.

Storage

Can be stored for 2 years in cool and dry places.

After filling: Observe shelf life of 1 to 2 weeks, depending on the paint system in use.

VOC-regulation

EU limit value for the product (cat. B/e): 840 g/l
This product contains max. 840 g/l of VOC.

Safety information

See safety data sheet