

Mipa WBS Reiniger-FINAL-Spray

Item no 21257 0000

Technical data sheet

mipa

Professional Coating Systems

page 1 / 2

Intended use

Mipa WBS Reiniger Final Spray Mipa WBS Reiniger Final Spray is a highly efficient waterborne cleaning and degreasing agent that is mild in odour and provides an anti-static effect on plastic parts. Thanks to the special gentle formulation Mipa WBS Reiniger Final Spray is perfectly suitable to be a part of the Mipa Scheinwerfer-Reparatursystem (repair kit for headlights). The plastic lenses of headlights are not harmed or dissolved.

Processing instructions



Substrate

Can be used on all common plastics
Paints and fillers

Pre-treatment / cleansing

-

Characteristics

Eliminates and avoids electrostatic charges
Gentle formulation and mild in odour
Cleaning agent for Mipa headlight repair system
Easy to use
Great time savings

Colour / gloss level

colourless




Preparation

Before use, shake can vigorously for 1 - 2 min!



Application

-



Flash-off time

-




After use

-

Version: en 0322

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

MIPA SE · Am Oberen Moos 1 · D-84051 Essenbach · Tel.: +49(0)87 03/922-0 · Fax: +49(0)87 03/922-100 · mipa@mipa-paints.com · www.mipa-paints.com



Drying time at 20 °C

-

Processing conditions From +10 °C and up to 80 % relative air humidity. Ensure adequate air ventilation.

Storage Can be stored for 2 years in cool and dry places.

VOC-regulation EU limit value for this product (cat. B/e): 840 g/l
This product contains max. 715 g/l of VOC.

Safety information See safety data sheet