

Mipa Handspachtel fein

en 3/1221

page 1 of 2

Technical data sheet

Product description

Intended use: This self-adhesive, fine-grained putty is used for interior full-area

manual putty work on ceilings and walls in renovation work and for new buildings. Mipa Handspachtel fein is ready to use and guarantees a simple and even surface without shrinkage.

Characteristics: excellent adhesion

especially easy to apply

- high vertical stability, slight sagging, does not detach from the

substrate when smoothing

- can be spread to zero, for coat thicknesses 0 - 6 mm

- very good sanding properties

- free from solvents and plasticizer, low emission

- free from substances causing magic dust

- non-combustible (class A2-s1,d0 according to EN 13501-1 as

per classification report)

Content as per VDL Directive 01:

(Association of German paint

industry)

Polymeric dispersion, white Dolomite marble, silica-based filling

materials. water, additives, preservatives

Colour: White

Specifications: specific weight: approx. 1,72 g/cm³ **DIN 51757**

pH value: approx. 9 **DIN 53785**

Storage: at least 2 years in unopened original container, store frost-free

and protected from direct sunlight at a temperature of +5 °C to

max. +30 °C.

Application

Processing conditions: Do not apply at a substrate and ambient temperature of below

+5°C.

Old and new plasters (mortar group PI, PII, PIII, PIVa,b,c, CS Suitable substrates:

> II, CS IV), concrete, gas concrete, lime sand brick, fibre cement, gypsum cardboard, fibreglass as well as well adherent old

paintworks.

Substrate preparation: The substrates must be dry, solid and clean. Remove loose

> parts, old glue-bound distemper paints, wallpaper, dirt, grease, wax and mould release agents (e.g. formwork release oil).

Mineral substrates: Remove dust and loose parts. Prime very absorbent, chalking and friable substrates with Mipa Tiefgrund

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.



Mipa Handspachtel fein

en 3/1221

page 2 of 2

Technical data sheet

Application: Stir Mipa Handspachtel fein and apply by means of a smoothing

trowel. Irregularities can be smoothed wet or by means of a felt

float. Max. coat thickness per operation: 5 – 6 mm

Dilution: Mipa Handspachtel fein is ready for use.

Drying time: at 20 °C and 65 % relative air humidity approx. 4 - 7 hours de-

pending on the applied layer thickness, the nature of the substrate and the environmental conditions. Do not apply subsequent coats of paint or glue until the smoothed surfaces are

completely dry!

Spreading rate: Approx. 1,7 kg/m² per mm applied

Special notes

Stir well before use. Apply and smooth Mipa Handspachtel fein with a smoothing trowel made of stainless steel. Prime with Mipa Tiefgrund LF the filled and sanded surfaces before redecorating with wallpaper or paint.

Safety advice

Consider general hygienic rules. Do not empty into drains, watercourses or soil. Ensure thorough ventilation during and after the application. We recommend wearing protective goggles and a dust mask during sanding work.

Cleaning of tools

Clean tools with water immediately after user or in case of longer interruption of work.

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.