

Safety data sheet Professional Coating Systems according to 1907/2006/EC, Article 31 Printing date 10.01.2024 Version number 17 (replaces version 16) Revision: 10.01.2024 SECTION 1: Identification of the substance/mixture and of the company/ undertaking · 1.1 Product identifier Trade name: Mipa Rapidprimer-Spray · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Priming · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: MIPA SE Am Oberen Moos 1 D-84051 Essenbach Tel.: +49 8703 92 20 Fax.: +49 8703 92 21 00 e-mail: sdb-registratur@mipa-paints.com www.mipa-paints.com • 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP) **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 flame Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. Eye Irrit. 2 H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness. Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. · Hazard pictograms



· Signal word Danger

 Hazard-determining components of labelling: acetone Bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight 700-1100) 1-methoxy-2-propanol n-Butyl acetate · Hazard statements H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. H319 Causes serious eye irritation.

(Contd. on page 2)



Safety data sheet according to 1907/2006/EC, Article 31

according to 1907/2006/EC, Article 31 Version number 17 (replaces version 16)

Revision: 10.01.2024

Printing date 10.01.2024

Trade name: Mipa Rapidprimer-Spray

| | (Contd. of page 1) | | | | |
|-------------|---|--|--|--|--|
| H317 | May cause an allergic skin reaction. | | | | |
| H336 | May cause drowsiness or dizziness. | | | | |
| H412 | Harmful to aquatic life with long lasting effects. | | | | |
| · Precautio | Precautionary statements | | | | |
| P101 | If medical advice is needed, have product container or label at hand. | | | | |
| P102 | Keep out of reach of children. | | | | |
| P103 | Read carefully and follow all instructions. | | | | |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition | | | | |
| | sources. No smoking. | | | | |
| P211 | Do not spray on an open flame or other ignition source. | | | | |
| P251 | Do not pierce or burn, even after use. | | | | |
| P305+P3 | 51+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact | | | | |
| | lenses, if present and easy to do. Continue rinsing. | | | | |
| P410+P4 | 12 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. | | | | |
| P501 | Dispose of contents/container in accordance with local/regional/national/ | | | | |
| | international regulations. | | | | |
| · Additiona | al information: | | | | |
| EUH066 P | Repeated exposure may cause skin dryness or cracking. | | | | |
| | f explosive mixtures possible without sufficient ventilation. | | | | |
| | Contains epoxy constituents. May produce an allergic reaction. | | | | |
| · 2.3 Other | | | | | |
| | of PBT and vPvB assessment | | | | |
| | | | | | |

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

| · Dangerous components: | dimethylathor | 25 500/ |
|--|--|------------------|
| CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37 | dimethyl ether | 25-50% |
| CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49 | acetone | <i>≥</i> 10-<15% |
| CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35 | 1-methoxy-2-propanol Flam. Liq. 3, H226; () STOT SE 3, H336 | 2.5-<10% |
| CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29 | n-Butyl acetate | 5-<10% |
| CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32 | Xylene ♦ Flam. Liq. 3, H226; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ↑ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | 2.5-<5% |
| CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29 | 2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; () STOT SE 3, H336 | <2.5% |
| CAS: 25068-38-6 | Bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight 700-1100) Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 | <i>≥</i> 1-<2.5% |

GB —



according to 1907/2006/EC, Article 31

Printing date 10.01.2024

Version number 17 (replaces version 16)

Revision: 10.01.2024

Trade name: Mipa Rapidprimer-Spray

| | | (Contd. of page 2) |
|--|---|---------------------|
| CAS: 7779-90-0 | Trizinc bis(orthophosphate) | <i>≥</i> 0.25-<2.5% |
| EINECS: 231-944-3 Reg.nr.: 01-2119485044-40 | local Acute 1, H400; Aquatic Chronic 1, H410 | |
| CAS: 162627-17-0 | Fatty acids, C18-unsatd., dimers, reaction products with | |
| EC number: 605-296-0 | N, N-dimethyl-1, 3-propanediamine and 1, 3- | |
| Reg.nr.: 01-2119970640-38 | propanediamine | |
| | 🚸 Skin Sens. 1A, H317 | |
| Additional information: Ea | r the wording of the listed hazard phrases refer to section | 16 |

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately rinse with water.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • After swallowing: If symptoms persist consult doctor.

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device. Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

(Contd. on page 4)

GB



Printing date 10.01.2024

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 17 (replaces version 16)

Revision: 10.01.2024

Trade name: Mipa Rapidprimer-Spray

See Section 13 for disposal information.

(Contd. of page 3)

SECTION 7: Handling and storage

• **7.1 Precautions for safe handling** Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility: Store away from foodstuffs.

- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

107-98-2 1-methoxy-2-propanol

WEL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Sk

123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

1330-20-7 Xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

108-65-6 2-Methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

(Contd. on page 5)

GB -



according to 1907/2006/EC, Article 31 Version number 17 (replaces version 16)

Revision: 10.01.2024

Printing date 10.01.2024

Trade name: Mipa Rapidprimer-Spray

(Contd. of page 4) Ingredients with biological limit values: 1330-20-7 Xylene BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid • Additional information: The lists valid during the making were used as basis. · 8.2 Exposure controls · Appropriate engineering controls No further data; see section 7. · Individual protection measures, such as personal protective equipment • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection

Safety glasses



Tightly sealed goggles

SECTION 9: Physical and chemical properties

[.] 9.1 Information on basic physical and chemical properties

- General Information
- · Physical state
- · Colour:
- · Odour:

Aerosol According to product specification Characteristic

(Contd. on page 6)

GB



Safety data sheet according to 1907/2006/EC, Article 31

Revision: 10.01.2024

Printing date 10.01.2024

Version number 17 (replaces version 16)

| | (Contd. of page |
|--|---|
| Odour threshold: | Not determined. |
| Melting point/freezing point: | Undetermined. |
| Boiling point or initial boiling point and | |
| boiling range | -24.9 °C |
| Flammability | Not applicable. |
| Lower and upper explosion limit | |
| Lower: | 2.6 Vol % |
| Upper: | 18.6 Vol % |
| Flash point: | <0 °C (DIN EN ISO 1523:2002) |
| Auto-ignition temperature: | 235 °C (DIN 51794) |
| Decomposition temperature: | Not determined. |
| рН | Not determined. |
| , Viscosity: | |
| Kinematic viscosity | Not determined. |
| Dynamic: | Not determined. |
| Solubility | |
| water: | Not miscible or difficult to mix. |
| Partition coefficient n-octanol/water (log | |
| value) | Not determined. |
| value) Vapour pressure at 20 °C: | 5,200 hPa |
| | 0,200 HF a |
| <i>Density and/or relative density Density at 20 °C:</i> | 0.840 a/cm3 (DIN EN ISO 2011 1) |
| Relative density | 0.849 g/cm ³ (DIN EN ISO 2811-1) |
| | Not determined. |
| Vapour density | Not determined. |
| 9.2 Other information | |
| Appearance: | · · · |
| Form: | Aerosol |
| Important information on protection of heal | lth |
| | |
| and environment, and on safety. | |
| and environment, and on safety. Ignition temperature: | Product is not selfigniting. |
| and environment, and on safety. | Product is not selfigniting. In use, may form flammable/explosive vapour-a |
| and environment, and on safety. Ignition temperature: Explosive properties: | Product is not selfigniting. |
| and environment, and on safety. Ignition temperature: | Product is not selfigniting. In use, may form flammable/explosive vapour-a mixture. |
| and environment, and on safety. Ignition temperature: Explosive properties: | Product is not selfigniting. In use, may form flammable/explosive vapour-a mixture. 0.0 % |
| and environment, and on safety. Ignition temperature: Explosive properties: Solvent content: | Product is not selfigniting. In use, may form flammable/explosive vapour-a mixture. |
| and environment, and on safety. Ignition temperature: Explosive properties: Solvent content: Water: | Product is not selfigniting. In use, may form flammable/explosive vapour-a mixture. 0.0 % |
| and environment, and on safety. Ignition temperature: Explosive properties: Solvent content: Water: VOC (EC) | Product is not selfigniting. In use, may form flammable/explosive vapour-a mixture. 0.0 % 78.80 % |
| and environment, and on safety. Ignition temperature: Explosive properties: Solvent content: Water: VOC (EC) Solids content (weight-%): | Product is not selfigniting. In use, may form flammable/explosive vapour-a mixture. 0.0 % 78.80 % |
| and environment, and on safety. Ignition temperature: Explosive properties: Solvent content: Water: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate | Product is not selfigniting. In use, may form flammable/explosive vapour-a mixture. 0.0 % 78.80 % 21.1 % Not applicable. |
| and environment, and on safety. Ignition temperature: Explosive properties: Solvent content: Water: VOC (EC) Solids content (weight-%): Change in condition | Product is not selfigniting. In use, may form flammable/explosive vapour-a mixture. 0.0 % 78.80 % 21.1 % Not applicable. |
| and environment, and on safety. Ignition temperature: Explosive properties: Solvent content: Water: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical haza classes | Product is not selfigniting. In use, may form flammable/explosive vapour-a mixture. 0.0 % 78.80 % 21.1 % Not applicable. |
| and environment, and on safety. Ignition temperature: Explosive properties: Solvent content: Water: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical haza classes Explosives | Product is not selfigniting. In use, may form flammable/explosive vapour-a mixture. 0.0 % 78.80 % 21.1 % Not applicable. Ind Void |
| and environment, and on safety. Ignition temperature: Explosive properties: Solvent content: Water: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical haza classes Explosives Flammable gases | Product is not selfigniting. In use, may form flammable/explosive vapour-a mixture. 0.0 % 78.80 % 21.1 % Not applicable. Ind Void |
| and environment, and on safety. Ignition temperature: Explosive properties: Solvent content: Water: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical haza classes Explosives | Product is not selfigniting. In use, may form flammable/explosive vapour-a mixture. 0.0 % 78.80 % 21.1 % Not applicable. Not applicable. Void Void Extremely flammable aerosol. Pressurise |
| and environment, and on safety. Ignition temperature: Explosive properties: Solvent content: Water: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical haza classes Explosives Flammable gases Aerosols | Product is not selfigniting. In use, may form flammable/explosive vapour-a mixture. 0.0 % 78.80 % 21.1 % Not applicable. Not applicable. Void Void Extremely flammable aerosol. Pressurise container: May burst if heated. |
| and environment, and on safety. Ignition temperature: Explosive properties: Solvent content: Water: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical haza classes Explosives Flammable gases Aerosols Oxidising gases | Product is not selfigniting. In use, may form flammable/explosive vapour-a mixture. 0.0 % 78.80 % 21.1 % Not applicable. Not applicable. Void Extremely flammable aerosol. Pressurise container: May burst if heated. Void |
| and environment, and on safety. Ignition temperature: Explosive properties: Solvent content: Water: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical haza classes Explosives Flammable gases Aerosols Oxidising gases Gases under pressure | Product is not selfigniting. In use, may form flammable/explosive vapour-a mixture. 0.0 % 78.80 % 21.1 % Not applicable. Ind Void Extremely flammable aerosol. Pressurise container: May burst if heated. Void Void |
| and environment, and on safety. Ignition temperature: Explosive properties: Solvent content: Water: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical haza classes Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids | Product is not selfigniting. In use, may form flammable/explosive vapour-a mixture. 0.0 % 78.80 % 21.1 % Not applicable. Not applicable. Ind Void Extremely flammable aerosol. Pressurise container: May burst if heated. Void Void Void Void Void |
| and environment, and on safety. Ignition temperature: Explosive properties: Solvent content: Water: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical haza classes Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids | Product is not selfigniting. In use, may form flammable/explosive vapour-a mixture. 0.0 % 78.80 % 21.1 % Not applicable. Ind Void Extremely flammable aerosol. Pressurise container: May burst if heated. Void Void Void Void Void Void Void |
| and environment, and on safety. Ignition temperature: Explosive properties: Solvent content: Water: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical haza classes Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures | Product is not selfigniting. In use, may form flammable/explosive vapour-a mixture. 0.0 % 78.80 % 21.1 % Not applicable. Ind Void Extremely flammable aerosol. Pressurise container: May burst if heated. Void Void Void Void Void Void Void Void |
| and environment, and on safety. Ignition temperature: Explosive properties: Solvent content: Water: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical haza classes Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids | Product is not selfigniting. In use, may form flammable/explosive vapour-a mixture. 0.0 % 78.80 % 21.1 % Not applicable. Ind Void Extremely flammable aerosol. Pressurise container: May burst if heated. Void Void Void Void Void Void Void Void |
| and environment, and on safety. Ignition temperature: Explosive properties: Solvent content: Water: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical haza classes Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids | Product is not selfigniting. In use, may form flammable/explosive vapour-a mixture. 0.0 % 78.80 % 21.1 % Not applicable. Ind Void Extremely flammable aerosol. Pressurise container: May burst if heated. Void Void Void Void Void Void Void Void |
| and environment, and on safety. Ignition temperature: Explosive properties: Solvent content: Water: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical haza classes Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures | Product is not selfigniting. In use, may form flammable/explosive vapour-a mixture. 0.0 % 78.80 % 21.1 % Not applicable. Ind Void Extremely flammable aerosol. Pressurise container: May burst if heated. Void Void Void Void Void Void Void Void |
| and environment, and on safety. Ignition temperature: Explosive properties: Solvent content: Water: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical haza classes Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Self-heating substances and mixtures Substances and mixtures, which emit | Product is not selfigniting. In use, may form flammable/explosive vapour-a mixture. 0.0 % 78.80 % 21.1 % Not applicable. Not applicable. Void Extremely flammable aerosol. Pressurise container: May burst if heated. Void Void Void Void Void Void Void Void |
| and environment, and on safety. Ignition temperature: Explosive properties: Solvent content: Water: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical haza classes Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures | Product is not selfigniting. In use, may form flammable/explosive vapour-a mixture. 0.0 % 78.80 % 21.1 % Not applicable. Ind Void Extremely flammable aerosol. Pressurise container: May burst if heated. Void Void Void Void Void Void Void Void |



according to 1907/2006/EC, Article 31

Revision: 10.01.2024

Printing date 10.01.2024

Version number 17 (replaces version 16)

Trade name: Mipa Rapidprimer-Spray

| | | (Contd. of page 6) |
|---|------|--------------------|
| · Oxidising liquids | Void | |
| • Oxidising solids | Void | |
| · Organic peroxides | Void | |
| · Corrosive to metals | Void | |
| Desensitised explosives | Void | |

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

Possible in traces. Nitrogen oxides Hydrogen chloride (HCl) Carbon monoxide Nitrogen oxides (NOx)

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

Serious eye damage/irritation Causes serious eye irritation.

- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- **STOT-single exposure** May cause drowsiness or dizziness.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Not applicable.
- 12.6 Endocrine disrupting properties
- For information on endocrine disrupting properties see section 11.
- [•] 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) : hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

(Contd. on page 8)



Printing date 10.01.2024

Safety data sheet

according to 1907/2006/EC, Article 31

Version number 17 (replaces version 16)

Revision: 10.01.2024

Trade name: Mipa Rapidprimer-Spray

(Contd. of page 7)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

| SECTION 14: Transport informati | ion |
|--|--|
| · 14.1 UN number or ID number · ADR, IMDG, IATA | UN1950 |
| · 14.2 UN proper shipping name · ADR · IMDG | UN1950 AEROSOLS AEROSOLS |
| | AEROSOLS, flammable |
| 14.3 Transport hazard class(es) | |
| ADR | |
| | |
| · Class | 2 5F Gases. |
| ·Label | 2.1 |
| | |
| · Class | 2.1 Gases. |
| · Label | 2.1 |
| · 14.4 Packing group · ADR, IMDG, IATA | Void |
| · 14.5 Environmental hazards: · Marine pollutant: | No |
| · 14.6 Special precautions for user | Warning: Gases. |
| Hazard identification number (Kemler c | |
| · EMS Number: · Stowage Code | F-D,S-U SW1 Protected from sources of heat. |
| Stowage Code | SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. |
| · Segregation Code | SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from |
| | class 1 except for division 1.4. |
| | For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of |
| | (Contd. on page |



according to 1907/2006/EC, Article 31

Printing date 10.01.2024

Version number 17 (replaces version 16)

Revision: 10.01.2024

Trade name: Mipa Rapidprimer-Spray

| | (Contd. of page 8 |
|--|--|
| | class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. |
| 14.7 Maritime transport in bulk according to IMO instruments | Not applicable. |
| · Transport/Additional information: | |
| ADR | |
| · Limited quantities (LQ) | 1L |
| Transport category | 2 |
| Tunnel restriction code | D |
| ·IMDG | |
| Limited quantities (LQ) | 1L |
| · UN "Model Regulation": | UN 1950 AEROSOLS, 2.1 |

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P3a FLAMMABLE AEROSOLS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· National regulations:

· Additional classification according to Decree on Hazardous Materials, Annex II:

Class Share in %

• **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

(Contd. on page 10)



Safety data sheet according to 1907/2006/EC, Article 31

Revision: 10.01.2024

Printing date 10.01.2024

Version number 17 (replaces version 16)

| Trade name: Mipa | Rapidprimer-Spray |
|------------------|-------------------|
|------------------|-------------------|

| | (Contd. of page 9) |
|--|------------------------|
| EUH066 Repeated exposure may cause skin dryness or cracking. | · · · · · / |
| EUH205 Contains epoxy constituents. May produce an allergic reaction. | |
| Classification according to Regulation (EC) No 1272/2008 | |
| | na aubatanaa data |
| The classification of the mixture is generally based on the calculation method usin | ng substance data |
| according to Regulation (EC) No 1272/2008. | |
| · Abbreviations and acronyms: | |
| RID: Règlement international concernant le transport des marchandises dangereuses par chemi | in de fer (Regulations |
| Concerning the International Transport of Dangerous Goods by Rail) | |
| ICAO: International Civil Aviation Organisation | |
| ADR: Accord relatif au transport international des marchandises dangereuses par route (European A | Agreement Concerning |
| the International Carriage of Dangerous Goods by Road) | |
| IMDG: International Maritime Code for Dangerous Goods | |
| IATA: International Air Transport Association | |
| GHS: Globally Harmonised System of Classification and Labelling of Chemicals | |
| EINECS: European Inventory of Existing Commercial Chemical Substances | |
| ELINCS: European List of Notified Chemical Substances | |
| CAS: Chemical Abstracts Service (division of the American Chemical Society) | |
| VOC: Volatile Organic Compounds (USA, EU) | |
| PBT: Persistent, Bioaccumulative and Toxic | |
| vPvB: very Persistent and very Bioaccumulative | |
| Flam. Gas 1A: Flammable gases – Category 1A | |
| Aerosol 1: Aerosols – Category 1 | |
| Press. Gas (Liq.): Gases under pressure – Liquefied gas | |
| Flam. Liq. 2: Flammable liquids – Category 2 | |
| Flam. Liq. 3: Flammable liquids – Category 3 | |
| Acute Tox. 4: Acute toxicity – Category 4 | |
| Skin Irrit. 2: Skin corrosion/irritation – Category 2 | |
| Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 | |
| Skin Sens. 1: Skin sensitisation – Category 1 | |
| Skin Sens. 1A: Skin sensitisation – Category 1A | |
| STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 | |
| STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 | |
| Asp. Tox. 1: Aspiration hazard – Category 1 | |
| Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 | |
| Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 | |
| | |
| • * Data compared to the previous version altered. | |
| | GB |