Revision: 20.06.2024



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 20.06.2024

Version number 157 (replaces version 156)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Mipa Silikonentferner
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC9a Coatings and paints, thinners, paint removers
- · Application of the substance / the mixture Cleaning agent/ Cleaner
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49 8703 92 20

Fax.: +49 8703 92 21 00

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

· 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



STOT SE 3

H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 20.06.2024 Version number 157 (replaces version 156) Revision: 20.06.2024

Trade name: Mipa Silikonentferner

(Contd. of page 1)

· Hazard pictograms









GHS02 GHS07 GHS08 G

· Signal word Danger

· Hazard-determining components of labelling:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

· Hazard statements

H225 Highly flammable liquid and vapour. H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

·D	angerous components:		
	C number: 920-750-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	50-100%
R	Reg.nr.: 01-2119473851-33	♠ Flam. Liq. 2, H225; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H336, EUH066	
	C number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	10-25%
		♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336, EUH066	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

GB



according to Regulation (EC) No 1907/2006, Article 31

Printing date 20.06.2024 Version number 157 (replaces version 156) Revision: 20.06.2024

Trade name: Mipa Silikonentferner

(Contd. of page 2)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Seek immediate medical advice.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents: Alcohol resistant foam
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- Requirements to be met by storerooms and receptacles: Store in a cool location.

(Contd. on page 4)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 20.06.2024 Version number 157 (replaces version 156) Revision: 20.06.2024

Trade name: Mipa Silikonentferner

(Contd. of page 3)

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: > 0.4 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Breakthrough time of glove material Value for the permeation: Level \leq 3
- · Eye/face protection



Tightly sealed goggles



according to Regulation (EC) No 1907/2006, Article 31

Printing date 20.06.2024 Version number 157 (replaces version 156) Revision: 20.06.2024

Trade name: Mipa Silikonentferner

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and

boiling range 100-140 °C (Hydrocarbons, C7-C9, n-alkanes,

isoalkanes, cyclics)

· Flammability Highly flammable.

· Lower and upper explosion limit

Lower: 0.9 Vol % (Hydrocarbons, C7-C9, n-alkanes,

isoalkanes, cyclics)

· Upper: 8 Vol % (Hydrocarbons, C7-C9, n-alkanes,

isoalkanes, cyclics) -8 °C (DIN 53213)

Flash point:

 Auto-ignition temperature:
 Decomposition temperature:
 pH

 Solution temperature:
 Not determined.
 Not determined.

· pH · Viscositv:

· Kinematic viscosity at 20 °C 10-15 s (DIN 53211/4)

· **Dynamic:** Not determined.

Solubility

water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value) Not determined.

· Vapour pressure at 20 °C: 2-3.5 hPa (Hydrocarbons, C7-C9, n-alkanes,

isoalkanes, cyclics)

· Density and/or relative density

Density at 20 °C: 0.743 g/cm³ (DIN 53217)

Relative densityVapour densityNot determined.Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

· VOC (EC) 100.00 %
· Solids content (weight-%): 0.0 %

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard

classes

Explosives
Flammable gases
Aerosols
Oxidising gases
Gases under pressure

Void
Void
Void

(Contd. on page 6)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 20.06.2024 Version number 157 (replaces version 156) Revision: 20.06.2024

Trade name: Mipa Silikonentferner

(Contd. of page 5)

	(Conta. or page 3)
· Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
· Substances and mixtures, which emit	
flammable gases in contact with water	Void
· Oxidising liquids	Void
Oxidising solids	Void
· Organic peroxides	Void
Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- Aspiration hazard May be fatal if swallowed and enters airways.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation): hazardous for water

(Contd. on page 7)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 20.06.2024 Version number 157 (replaces version 156) Revision: 20.06.2024

Trade name: Mipa Silikonentferner

(Contd. of page 6)

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

·Label

· Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number ADR, IMDG, IATA	UN3295
14.2 UN proper shipping name ADR	UN3295 HYDROCARBONS, LIQUID, N.O. ENVIRONMENTALLY HAZARDOUS
IMDG	HYDROCARBONS, LIQUID, N.O. (Hydrocarbons, C7-C9), MARINE POLLUTANT
IATA	HYDROCARBONS, LIQUID, N.O.S.
14.3 Transport hazard class(es)	
Class Label	3 (F1) Flammable liquids. 3
IMDG	·
Class Label	3 Flammable liquids. 3
IATA	
Class	3 Flammable liquids.

3



according to Regulation (EC) No 1907/2006, Article 31

Printing date 20.06.2024 Version number 157 (replaces version 156) Revision: 20.06.2024

Trade name: Mipa Silikonentferner

	(Contd. of page
· 14.4 Packing group · ADR, IMDG, IATA	II .
· 14.5 Environmental hazards:	Product contains environmentally hazardou substances: Hydrocarbons, C7-C9
· Marine pollutant:	Yes Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user Hazard identification number (Kemler code):	
· EMS Number: · Stowage Category	F-E,S-D B
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Transport category	2
Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	1L
· UN "Model Regulation":	UN 3295 HYDROCARBONS, LIQUID, N.O.S. 3, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	50-100



according to Regulation (EC) No 1907/2006, Article 31

Printing date 20.06.2024 Version number 157 (replaces version 156) Revision: 20.06.2024

Trade name: Mipa Silikonentferner

(Contd. of page 8)

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids — Category 2

Flam. Liq. 3: Flammable liquids – Category 3 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

* Data compared to the previous version altered.