

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.01.2024

Version number 51 (replaces version 50)

Revision: 08.01.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Mipa Winner-Spray Acryl-Klarlack**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Clear coating material, Varnish
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MIPA SE
Am Oberen Moos 1
D-84051 Essenbach
Tel.: +49 8703 92 20
Fax.: +49 8703 92 21 00
e-mail: sdb-registratur@mipa-paints.com
www.mipa-paints.com
- **1.4 Emergency telephone number:** International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Irrit. 2	H319	Causes serious eye irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**
acetone
Hydrocarbons, C9, aromatics
2-Methoxy-1-methylethyl acetate
n-Butyl acetate
- **Hazard statements**
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319 Causes serious eye irritation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.01.2024

Version number 51 (replaces version 50)

Revision: 08.01.2024

Trade name: Mipa Winner-Spray Acryl-Klarlack

(Contd. of page 1)

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards
Results of PBT and vPvB assessment

 • **PBT:** Not applicable.

 • **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients
3.2 Mixtures

 • **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	25-50%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-21194869440-21	propane ⚠ Flam. Gas 1A, H220; Press. Gas (Liq.), H280	10-25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-31	butane, pure ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-25%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	2.5-<10%
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336, EUH066	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27	isobutane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	2.5-<10%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; ⚠ Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; ⚠ Acute Tox. 4, H332; ⚠ Skin Irrit. 2, H315; ⚠ Eye Irrit. 2, H319; STOT SE 3, H335	2.5-<5%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336, EUH066	2.5-<5%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.01.2024

Version number 51 (replaces version 50)

Revision: 08.01.2024

Trade name: Mipa Winner-Spray Acryl-Klarlack

(Contd. of page 2)

CAS: 100-41-4

EINECS: 202-849-4

Reg.nr.: 01-2119489370-35

Ethylbenzene

⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412

<2.5%

 · **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

 · **4.1 Description of first aid measures**

 · **After inhalation:** Supply fresh air; consult doctor in case of complaints.

 · **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

 · **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

 · **After swallowing:** Seek immediate medical advice.

 · **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

 · **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

 · **5.1 Extinguishing media**

 · **Suitable extinguishing agents:**

 CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

 · **5.2 Special hazards arising from the substance or mixture**

No further relevant information available.

 · **5.3 Advice for firefighters**

 · **Protective equipment:**

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

 · **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

 · **6.2 Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

 · **6.3 Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

 · **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

 · **7.1 Precautions for safe handling**

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.01.2024

Version number 51 (replaces version 50)

Revision: 08.01.2024

Trade name: Mipa Winner-Spray Acryl-Klarlack

(Contd. of page 3)

- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 2 B
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

 · **8.1 Control parameters**

 · **Ingredients with limit values that require monitoring at the workplace:**
67-64-1 acetone

WEL	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
-----	--

106-97-8 butane, pure

WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

108-65-6 2-Methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
-----	--

1330-20-7 Xylene

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	--

123-86-4 n-Butyl acetate

WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
-----	---

100-41-4 Ethylbenzene

WEL	Short-term value: 552 mg/m ³ , 125 ppm Long-term value: 441 mg/m ³ , 100 ppm Sk
-----	---

 · **Ingredients with biological limit values:**
1330-20-7 Xylene

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

 · **Additional information:** The lists valid during the making were used as basis.

 · **8.2 Exposure controls**

 · **Appropriate engineering controls** No further data; see section 7.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.01.2024

Version number 51 (replaces version 50)

Revision: 08.01.2024

Trade name: Mipa Winner-Spray Acryl-Klarlack

(Contd. of page 4)

- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Avoid contact with the eyes.
 Avoid contact with the eyes and skin.
- **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- **Hand protection**
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**
 Butyl rubber, BR
 Recommended thickness of the material: ≥ 0.7 mm
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Breakthrough time of glove material** Value for the permeation: Level ≤ 2
- **Eye/face protection**
 Safety glasses



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Physical state** Aerosol
- **Colour:** According to product specification
- **Odour:** Characteristic
- **Odour threshold:** Not determined.
- **Melting point/freezing point:** Undetermined.
- **Boiling point or initial boiling point and boiling range** -44.5 °C (74-98-6 propane)
- **Flammability** Not applicable.
- **Lower and upper explosion limit**
- **Lower:** 1.5 Vol % (106-97-8 butane, pure)
- **Upper:** 13 Vol % (67-64-1 acetone)
- **Flash point:** -97 °C (DIN EN ISO 1523:2002)

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.01.2024

Version number 51 (replaces version 50)

Revision: 08.01.2024

Trade name: Mipa Winner-Spray Acryl-Klarlack

(Contd. of page 5)

· Auto-ignition temperature:	315 °C (DIN 51794, 108-65-6 2-Methoxy-1-methylethyl acetate)
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	8,300 hPa (74-98-6 propane)
· Vapour pressure at 50 °C:	800 hPa
· Density and/or relative density	
· Density at 20 °C:	0.715 g/cm ³ (DIN EN ISO 2811-1)
· Relative density	Not determined.
· Vapour density	Not determined.

9.2 Other information

· Appearance:	
· Form:	Aerosol
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	In use, may form flammable/explosive vapour-air mixture.
· Solvent content:	
· VOC (EC)	90.10 %
· Solids content (weight-%):	9.9 %
· Change in condition	
· Evaporation rate	Not applicable.

Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

GB

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.01.2024

Version number 51 (replaces version 50)

Revision: 08.01.2024

Trade name: Mipa Winner-Spray Acryl-Klarlack

(Contd. of page 6)

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **Aspiration hazard** May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) : hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

GB

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.01.2024

Version number 51 (replaces version 50)

Revision: 08.01.2024

Trade name: Mipa Winner-Spray Acryl-Klarlack

(Contd. of page 7)

SECTION 14: Transport information

· 14.1 UN number or ID number
· ADR, IMDG, IATA

UN1950

· 14.2 UN proper shipping name
· ADR
· IMDG
· IATA

UN1950 AEROSOLS
AEROSOLS
AEROSOLS, flammable

· 14.3 Transport hazard class(es)
· ADR



· Class
· Label

2 5F Gases.
2.1

· IMDG, IATA



· Class
· Label

2.1 Gases.
2.1

· 14.4 Packing group
· ADR, IMDG, IATA

Void

· 14.5 Environmental hazards:
· Marine pollutant:

No

· 14.6 Special precautions for user
· Hazard identification number (Kemler code): -
· EMS Number:
· Stowage Code

Warning: Gases.
F-D, S-U
SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2.
For WASTE AEROSOLS:
Segregation as for the appropriate subdivision of class 2.

· Segregation Code

· 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

· Transport/Additional information:

· ADR
· Limited quantities (LQ)

1L

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.01.2024

Version number 51 (replaces version 50)

Revision: 08.01.2024

Trade name: Mipa Winner-Spray Acryl-Klarlack

(Contd. of page 8)

· Transport category	2
· Tunnel restriction code	D

· IMDG	
· Limited quantities (LQ)	1L
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
 - **Directive 2012/18/EU**
 - **Named dangerous substances - ANNEX I** None of the ingredients is listed.
 - **Seveso category P3a** FLAMMABLE AEROSOLS
 - **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
 - **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
 - **National regulations:**
 - **Additional classification according to Decree on Hazardous Materials, Annex II:**
- | Class | Share in % |
|-------|------------|
| NK | 50-100 |
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.
- **Classification according to Regulation (EC) No 1272/2008**
- The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
- **Abbreviations and acronyms:**
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.01.2024

Version number 51 (replaces version 50)

Revision: 08.01.2024

Trade name: Mipa Winner-Spray Acryl-Klarlack

(Contd. of page 9)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Press. Gas (Liq.): Gases under pressure – Liquefied gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * **Data compared to the previous version altered.**

GB