

#### Printing date 28.11.2023

## Safety data sheet

according to 1907/2006/EC, Article 31 Version number 49 (replaces version 48)

Revision: 28.11.2023

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: Mipalux HS Mattlack schwarz
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- No further relevant information available.
- Application of the substance / the mixture Paint
- 1.3 Details of the supplier of the safety data sheet
   Manufacturer/Supplier: MIPA SE
   Am Oberen Moos 1
   D-84051 Essenbach
   Tel.: +49 8703 92 20
   Fax.: +49 8703 92 21 00
   e-mail: sdb-registratur@mipa-paints.com
   www.mipa-paints.com
- 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

#### **SECTION 2: Hazards identification**

• 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation.
- · Hazard pictograms



· Signal word Warning

· Hazard-determining components of labelling: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 1-methoxy-2-propanol n-Butyl acetate · Hazard statements H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. Read carefully and follow all instructions. P103 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 28.11.2023

Version number 49 (replaces version 48)

Revision: 28.11.2023

### Trade name: Mipalux HS Mattlack schwarz

	(Contd. of page 1)	
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.	
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.	
P303+P361+P35	3 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].	
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
P501	Dispose of contents/container in accordance with local/regional/national/ international regulations.	
· Additional inform	nation:	
EUH066 Repeated exposure may cause skin dryness or cracking.		
EUH208 Contains	s Neodecansäure, Cobalsalz. May produce an allergic reaction.	
· 2.3 Other hazard	ls	
· Results of PBT and vPvB assessment		
DDT Material		

· PBT: Not applicable.

·vPvB: Not applicable.

#### **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	10-25%
	♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336, EUH066	
CAS: 1330-20-7	Xylene	2.5-<5%
EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	♦ Flam. Liq. 3, H226; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ↑ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 107-98-2	1-methoxy-2-propanol	2.5-<10%
EINECS: 203-539-1 Reg.nr.: 01-2119457435-35	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336	
CAS: 123-86-4	n-Butyl acetate	1-<2.5%
EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	🚸 Flam. Liq. 3, H226; () STOT SE 3, H336, EUH066	
EC number: 918-481-9 Reg.nr.: 01-2119457273-39	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	<2.5%
-	🚯 Asp. Tox. 1, H304, EUH066	
	Neodecansäure, Cobalsalz	<i>≥</i> 0.1-<1%
	STOT RE 1, H372; (1) Acute Tox. 4, H302; Skin Sens. 1, H317; Aquatic Chronic 3, H412	

### SECTION 4: First aid measures

• 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

· After inhalation: Supply fresh air; consult doctor in case of complaints.

· After skin contact: Immediately rinse with water.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

# Professional Coating Systems

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.11.2023

Version number 49 (replaces version 48)

Revision: 28.11.2023

(Contd. of page 2)

Trade name: Mipalux HS Mattlack schwarz

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

## SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- No luither leevant information a
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
   See Section 7 for information on safe handling.
   See Section 8 for information on personal protection equipment.
   See Section 13 for disposal information.

## SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols. • Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)

GB



Printing date 28.11.2023

## Safety data sheet

according to 1907/2006/EC, Article 31 Version number 49 (replaces version 48)

Revision: 28.11.2023

## Trade name: Mipalux HS Mattlack schwarz

(Contd. of page 3)

SECTION	8: Exposure	controls/personal	protection

#### · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

#### 1330-20-7 Xylene

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm Long-term value: 220 mg/m<sup>3</sup>, 50 ppm Sk; BMGV

#### 107-98-2 1-methoxy-2-propanol

WEL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Sk

#### 123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

#### · Ingredients with biological limit values:

#### 1330-20-7 Xylene

BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

• Additional information: The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
- Immediately remove all solled and contaminated clothing
- Wash hands before breaks and at the end of work.

### · Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### Hand protection

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

GR



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.11.2023

Eye/face protection

Version number 49 (replaces version 48)

Revision: 28.11.2023

Trade name: Mipalux HS Mattlack schwarz

Tightly sealed goggles

(Contd. of page 4)

SECTION 9: Physical and chemical properties · 9.1 Information on basic physical and chemical properties · General Information · Physical state Fluid · Colour: According to product specification · Odour: Characteristic · Odour threshold: Not determined. • Melting point/freezing point: Undetermined. · Boiling point or initial boiling point and 155 °C (Hydrocarbons, C9-C11, n-alkanes, boiling range isoalkanes, cyclics, < 2% aromatics) · Flammability Flammable. · Lower and upper explosion limit 0.6 Vol % · Lower: · Upper: 8 Vol % 27 °C (DIN 53213) · Flash point: · Auto-ignition temperature: >200 °C (DIN 51794) · Decomposition temperature: Not determined. · pH Not determined. · Viscositv: · Kinematic viscosity at 20 °C 175 s (DIN 53211/4) Not determined. · Dynamic: · Solubility Not miscible or difficult to mix. · water: · Partition coefficient n-octanol/water (log Not determined. value) 3 hPa (Hydrocarbons, C9-C11, n-alkanes, · Vapour pressure at 20 °C: isoalkanes, cyclics, < 2% aromatics) Density and/or relative density Density at 20 °C: 1.075 g/cm3 (DIN 53217) · Relative density Not determined. Not determined. · Vapour density · 9.2 Other information · Appearance: Fluid · Form: · Important information on protection of health and environment, and on safety. · Ignition temperature: Product is not selfigniting. Product is not explosive. However, formation of Explosive properties: explosive air/vapour mixtures are possible. · Solvent content: · Water: 0.0 % · VOC (EC) 35.21 % · Solids content (weight-%): 64.8 % (Contd. on page 6)



according to 1907/2006/EC, Article 31 Version number 49 (replaces version 48)

Revision: 28.11.2023

Printing date 28.11.2023

#### Trade name: Mipalux HS Mattlack schwarz

		(Contd. of page 5)
· Change in condition		
· Evaporation rate	Not determined.	
· Information with regard to physical haz	ard	
classes		
· Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
· Oxidising gases	Void	
<sup>.</sup> Gases under pressure	Void	
· Flammable liquids	Flammable liquid and vapour.	
· Flammable solids	Void	
<sup>·</sup> Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
• Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

#### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

#### SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

(Contd. on page 7)

GB

according to 1907/2006/EC, Article 31

Printing date 28.11.2023

#### Version number 49 (replaces version 48)

Revision: 28.11.2023

#### Trade name: Mipalux HS Mattlack schwarz

(Contd. of page 6)

- 12.7 Other adverse effects
- Additional ecological information:
- · General notes:
- Water hazard class 1 (German Regulation) : slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

#### **SECTION 13: Disposal considerations**

#### · 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information	
· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name · ADR · IMDG, IATA	UN1263 PAINT PAINT
· 14.3 Transport hazard class(es)	
ADR	
· Class · Label	3 (F1) Flammable liquids. 3
· IMDG, IATA	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	
<ul> <li>14.5 Environmental hazards:</li> <li>Marine pollutant:</li> </ul>	No
<ul> <li>14.6 Special precautions for user</li> <li>Hazard identification number (Kemler code):</li> <li>EMS Number:</li> <li>Stowage Category</li> </ul>	Warning: Flammable liquids. 30 F-E, <u>S-E</u> A
<ul> <li>14.7 Maritime transport in bulk according to IMO instruments</li> </ul>	Not applicable.
	(Contd. on page 8)





according to 1907/2006/EC, Article 31

*Printing date 28.11.2023* 

Version number 49 (replaces version 48)

Revision: 28.11.2023

Trade name: Mipalux HS Mattlack schwarz

	(Contd. of page
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Transport category	3
• Tunnel restriction code	D/E
· Remarks:	≤450 l: -
· IMDG	
· Limited quantities (LQ)	5L
· Remarks:	<i>≤</i> 30 l: -
· UN "Model Regulation":	UN 1263 PAINT, 3, III

#### SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

• National regulations:

• Additional classification according to Decree on Hazardous Materials, Annex II:



· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H226 Flammable liquid and vapour.

- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 9)

GB -



according to 1907/2006/EC, Article 31

Printing date 28.11.2023

Version number 49 (replaces version 48)

Revision: 28.11.2023

#### Trade name: Mipalux HS Mattlack schwarz

(Contd. of page 8) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 \*\* Data compared to the previous version altered. GB