

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name: **Mipa EP 950-25 2K-EP-Härter**

1.2 Relevant identified uses of the substance or mixture and uses advised against  
No further relevant information available.

### 1.3 Details of the supplier of the safety data sheet

**Sector of Use**  
SU21 Consumer uses: Private households / general public / consumers  
SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites  
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

**Product category PC9a** Coatings and paints, thinners, paint removers

**Application of the substance / the mixture** Hardening agent/ Curing agent

### 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

### Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1

D-84051 Essenbach

Tel.: +49 8703 92 20

Fax.: +49 8703 92 21 00

e-mail: [sdb-registratur@mipa-paints.com](mailto:sdb-registratur@mipa-paints.com)

[www.mipa-paints.com](http://www.mipa-paints.com)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

GB

**Trade name: Mipa EP 950-25 2K-EP-Härter**

(Contd. of page 1)

**Hazard pictograms**



GHS02 GHS05 GHS07 GHS08

**Signal word Danger**

**Hazard-determining components of labelling:**

Polyaminoamide adduct

Butan-1-ol

Xylene

**Hazard statements**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

**2.3 Other hazards**

**Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

**3.2 Mixtures**

**Description:** Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**

	Polyaminoamide adduct ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	50-100%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	25-50%
CAS: 71-36-3 EINECS: 200-751-6 Reg.nr.: 01-2119484630-38	Butan-1-ol ⚠ Flam. Liq. 3, H226; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	≥3-<10%

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

GB

(Contd. on page 3)

## Safety data sheet

according to UK REACH

Printing date 22.08.2024

Version number 161 (replaces version 160)

Revision: 22.08.2024

**Trade name: Mipa EP 950-25 2K-EP-Härter**

(Contd. of page 2)

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralising agent.  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.

(Contd. on page 4)

GB

**Trade name: Mipa EP 950-25 2K-EP-Härter**

(Contd. of page 3)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

#### 1330-20-7 Xylene

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 220 mg/m<sup>3</sup>, 50 ppm  
Sk; BMGV

#### 71-36-3 Butan-1-ol

WEL Short-term value: 154 mg/m<sup>3</sup>, 50 ppm  
Sk

- **Ingredients with biological limit values:**

#### 1330-20-7 Xylene

BMGV 650 mmol/mol creatinine  
Medium: urine  
Sampling time: post shift  
Parameter: methyl hippuric acid

- **Additional information:** The lists valid during the making were used as basis.

### 8.2 Exposure controls

- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the eyes.  
Avoid contact with the eyes and skin.
- **Respiratory protection:**  
Filter A/P2 (EN 141, EN 143)



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

### Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)

**Trade name: Mipa EP 950-25 2K-EP-Härter**

(Contd. of page 4)

· **Material of gloves**

Fluorocarbon rubber (Viton)

Recommended thickness of the material:  $\geq 0.7$  mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Breakthrough time of glove material** Value for the permeation: Level  $\leq 6$

· **Eye/face protection**



Tightly sealed goggles

**SECTION 9: Physical and chemical properties**

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Fluid

· **Colour:**

According to product specification

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Undetermined.

· **Boiling point or initial boiling point and boiling range**

116-118 °C (71-36-3 Butan-1-ol)

· **Flammability**

Flammable.

· **Lower and upper explosion limit**

· **Lower:**

1.1 Vol % (1330-20-7 Xylene)

· **Upper:**

7 Vol % (1330-20-7 Xylene)

· **Flash point:**

27 °C (DIN 53213)

· **Auto-ignition temperature:**

340 °C (DIN 51794, 71-36-3 Butan-1-ol)

· **Decomposition temperature:**

Not determined.

· **pH**

Not determined.

· **Viscosity:**

· **Kinematic viscosity**

Not determined.

· **Dynamic at 20 °C:**

800-2,200 mPas

· **Solubility**

· **water:**

Not miscible or difficult to mix.

· **Partition coefficient n-octanol/water (log value)**

Not determined.

· **Vapour pressure at 20 °C:**

6.7-8.2 hPa (1330-20-7 Xylene)

· **Density and/or relative density**

· **Density at 20 °C:**

0.941 g/cm<sup>3</sup> (DIN 53217)

· **Relative density**

Not determined.

· **Vapour density**

Not determined.

· **9.2 Other information**

· **Appearance:**

· **Form:**

Fluid

· **Important information on protection of health and environment, and on safety.**

· **Ignition temperature:**

Product is not selfigniting.

· **Explosive properties:**

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 6)

**Trade name: Mipa EP 950-25 2K-EP-Härter**

(Contd. of page 5)

· <b>Solvent content:</b>	
· <b>VOC (EC)</b>	40.00 %
· <b>Solids content (weight-%):</b>	60.0 %
· <b>Change in condition</b>	
· <b>Evaporation rate</b>	Not determined.
· <b>Information with regard to physical hazard classes</b>	
· <b>Explosives</b>	Void
· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Void
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Flammable liquid and vapour.
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void
· <b>Desensitised explosives</b>	Void

## SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

## SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

### · LD/LC50 values relevant for classification:

#### 1330-20-7 Xylene

Oral	LD50	5,251 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	29 mg/l (rat)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 7)

## Safety data sheet

according to UK REACH

Printing date 22.08.2024

Version number 161 (replaces version 160)

Revision: 22.08.2024

**Trade name: Mipa EP 950-25 2K-EP-Härter**

(Contd. of page 6)

### 11.2 Information on other hazards

#### Endocrine disrupting properties

None of the ingredients is listed.

## SECTION 12: Ecological information

### 12.1 Toxicity

**Aquatic toxicity:** No further relevant information available.

**12.2 Persistence and degradability** No further relevant information available.

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

### 12.5 Results of PBT and vPvB assessment

**PBT:** Not applicable.

**vPvB:** Not applicable.

### 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

### 12.7 Other adverse effects

#### Additional ecological information:

#### General notes:

Water hazard class 2 (German Regulation) : hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

#### Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.

## SECTION 14: Transport information

### 14.1 UN number or ID number

#### ADR, IMDG, IATA

UN1263

### 14.2 UN proper shipping name

#### ADR

UN1263 PAINT RELATED MATERIAL

#### IMDG, IATA

PAINT RELATED MATERIAL

### 14.3 Transport hazard class(es)

#### ADR



#### Class

3 (F1) Flammable liquids.

(Contd. on page 8)

## Safety data sheet

according to UK REACH


Printing date 22.08.2024

Version number 161 (replaces version 160)

Revision: 22.08.2024

**Trade name: Mipa EP 950-25 2K-EP-Härter**

(Contd. of page 7)

· <b>Label</b>	3
· <b>IMDG, IATA</b>	
	
· <b>Class</b>	3 Flammable liquids.
· <b>Label</b>	3
· <b>14.4 Packing group</b>	
· <b>ADR, IMDG, IATA</b>	III
· <b>14.5 Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>14.6 Special precautions for user</b>	Warning: Flammable liquids.
· <b>Hazard identification number (Kemler code):</b>	30
· <b>EMS Number:</b>	F-E, S-E
· <b>Stowage Category</b>	A
· <b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Transport category</b>	3
· <b>Tunnel restriction code</b>	D/E
· <b>Remarks:</b>	≤ 450 l: 2.2.3.1.5 ADR
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Remarks:</b>	≤ 450 l: 2.3.2.5 IMDG-Code
· <b>UN "Model Regulation":</b>	UN 1263 PAINT RELATED MATERIAL, 3, III

### SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category P5c** FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

(Contd. on page 9)

## Safety data sheet

according to UK REACH

Printing date 22.08.2024

Version number 161 (replaces version 160)

Revision: 22.08.2024

**Trade name: Mipa EP 950-25 2K-EP-Härter**

(Contd. of page 8)

· **Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t**

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials, Annex II:**

Class	Share in %
NK	25-50

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· **Classification according to Regulation (EC) No 1272/2008**

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

· **\* Data compared to the previous version altered.**