

according to UK REACH

Version number 17 (replaces version 16)

Revision: 02.10.2024

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: Mipalin
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- Sector of Use
- SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- SU21 Consumer uses: Private households / general public / consumers
- SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- Product category PC9a Coatings and paints, thinners, paint removers
- · Application of the substance / the mixture Paint
- · 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: MIPA SE Am Oberen Moos 1 D-84051 Essenbach Tel.: +49 8703 92 20 Fax.: +49 8703 92 21 00 e-mail: sdb-registratur@mipa-paints.com www.mipa-paints.com

• 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

#### **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

#### · 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



· Signal word Warning

Hazard-determining components of labelling:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 2-Methoxy-1-methylethyl acetate 1-methoxy-2-propanol n-Butyl acetate Hazard statements H226 Flammable liquid and vapour.

GB



#### Safety data sheet according to UK REACH

according to UK REACH Version number 17 (replaces version 16)

Revision: 02.10.2024

Trade name: Mipalin

	(Contd. of page 1)
H336 May cause	drowsiness or dizziness.
· Precautionary s	tatements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P35	3 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P501	Dispose of contents/container in accordance with local/regional/national/ international regulations.
· Additional infor	mation:
EUH066 Repeate	ed exposure may cause skin dryness or cracking.
EUH208 Contain	s Neodecanoic acid, cobalt salt. May produce an allergic reaction.
EUH211 Warning	g! Hazardous respirable droplets may be formed when sprayed. Do not breathe
spray or	r mist.
· 2.3 Other hazard	ds and a second s
<ul> <li>Results of PBT a</li> </ul>	and vPvB assessment
• PBT: Not applica	
· vPvB: Not applic	able.

### SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336, EUH066	10-25%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226;	2.5-<10%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene ♦ Flam. Liq. 3, H226; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ↑ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-<10%
CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35	1-methoxy-2-propanol	2.5-<10%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate ♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336, EUH066	1-<2.5%
CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47	2-Butoxyethyl acetate Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	1-<2.5%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	Ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	<2.5%



according to UK REACH

Version number 17 (replaces version 16)

Revision: 02.10.2024

Trade name: Mipalin

Printing date 02.10.2024

Neodecanoic acid, cobalt salt

(Contd. of page 2) ≥0.1-<1%

CAS: 27253-31-2 EINECS: 248-373-0 Reg.nr.: 01-2119970733-31

STOT RE 1, H372; 🗘 Acute Tox. 4, H302; Skin Sens.

Sens.

Reg.nr.: 01-2119970733-31 1, H317; Aquatic Chronic 3, H412 Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • After swallowing: If symptoms persist consult doctor.

• **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

#### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### **SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

• **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

• Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

(Contd. on page 4)



according to UK REACH

Printing date 02.10.2024

#### Version number 17 (replaces version 16)

Revision: 02.10.2024

Trade name: Mipalin

(Contd. of page 3)

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Store away from foodstuffs.

· Further information about storage conditions: Keep container tightly sealed.

· Storage class: 3

• 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

-	dients with limit values that require monitoring at the workplace: 5-6 2-Methoxy-1-methylethyl acetate	
	Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk	
1330	20-7 Xylene	
WEL	Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV	
107-9	8-2 1-methoxy-2-propanol	
WEL	Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Sk	
123-8	6-4 n-Butyl acetate	
WEL	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm	
112-0	7-2 2-Butoxyethyl acetate	
WEL	Short-term value: 332 mg/m³, 50 ppm Long-term value: 133 mg/m³, 20 ppm Sk	
100-4	1-4 Ethylbenzene	
WEL	Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk	
Ingre	dients with biological limit values:	
1330	20-7 Xylene	
BMG	V 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid	
Addi	tional information: The lists valid during the making were used as basis.	
Appr Indiv Gene	xposure controls opriate engineering controls No further data; see section 7. idual protection measures, such as personal protective equipment ral protective and hygienic measures: diately remove all soiled and contaminated clothing	

(Contd. on page 5)

GB



## Safety data sheet

according to UK REACH

Version number 17 (replaces version 16) Re

Revision: 02.10.2024

(Contd. of page 4)

Trade name: Mipalin

· Respiratory protection:

Filter A/P2 (EN 141, EN 143)



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

• Material of gloves

Fluorocarbon rubber (Viton)

Recommended thickness of the material:  $\geq$  0.7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

For the mixture of chemicals the penetration time has to be at least 30 minutes (Permeation according to EN 374 Part 3: Level 2).

#### · Eye/face protection



Tightly sealed goggles

### **SECTION 9: Physical and chemical properties**

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Physical state
- · Colour:
- · Odour:
- Odour threshold:
- *Melting point/freezing point:*
- Boiling point or initial boiling point and boiling range
- · Flammability
- Lower and upper explosion limit
- · Lower:
- · Upper:
- · Flash point:
- Auto-ignition temperature:
- · Decomposition temperature:
- ∙pH
- · Viscosity:
- Kinematic viscosity at 20 °C

Fluid According to product specification Characteristic Not determined. Undetermined.

137-143 °C (1330-20-7 Xylene) Flammable.

0.6 Vol % 8 Vol % 29 °C (DIN 53213) 315 °C (DIN 51794, 108-65-6 2-Methoxy-1methylethyl acetate) Not determined. Not determined.

120-130 s (DIN 53211/4)

(Contd. on page 6)



# Safety data sheet according to UK REACH

Version number 17 (replaces version 16)

Revision: 02.10.2024

Trade name: Mipalin

	(Contd. of page 5
Dynamic:	Not determined.
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log	
value)	Not determined.
Vapour pressure at 20 °C:	6.7-8.2 hPa (1330-20-7 Xylene)
Density and/or relative density	······································
Density at 20 °C:	1.029 g/cm³ (DIN 53217)
Relative density	Not determined.
Vapour density	Not determined.
· · ·	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of hea	aith
and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
Solvent content:	
VOC (EC)	43.44 %
Solids content (weight-%):	56.6 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical haz	ard
classes	
Explosives	Void
Flammable gases	Void
Aerosols	
	Void
Oxidising gases	Void
Oxidising gases Gases under pressure	Void Void
Oxidising gases Gases under pressure Flammable liquids	Void Void Flammable liquid and vapour.
Oxidising gases Gases under pressure Flammable liquids Flammable solids	Void Void Flammable liquid and vapour. Void
Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures	Void Void Flammable liquid and vapour. Void Void
Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids	Void Void Flammable liquid and vapour. Void Void Void
Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids	Void Void Flammable liquid and vapour. Void Void Void Void
Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures	Void Void Flammable liquid and vapour. Void Void Void
Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit	Void Void Flammable liquid and vapour. Void Void Void Void Void
Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water	Void Void Flammable liquid and vapour. Void Void Void Void Void
Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids	Void Void Flammable liquid and vapour. Void Void Void Void Void Void Void
Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water	Void Void Flammable liquid and vapour. Void Void Void Void Void Void Void Void
Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids Oxidising solids Organic peroxides	Void Void Flammable liquid and vapour. Void Void Void Void Void Void Void
Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids Oxidising solids	Void Void Flammable liquid and vapour. Void Void Void Void Void Void Void Void

## SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.

· 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 7)



according to UK REACH

Version number 17 (replaces version 16)

Revision: 02.10.2024

Trade name: Mipalin

Printing date 02.10.2024

· 10.6 Hazardous decomposition products: Carbon monoxide

### SECTION 11: Toxicological information

- $\cdot$  11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.

#### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Endocrine disrupting properties
- For information on endocrine disrupting properties see section 11.
- <sup>•</sup> 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) : hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

### SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

tion	
UN1263	
UN1263 PAINT	
PAINT	
	UN1263 UN1263 PAINT

(Contd. of page 6)



## Safety data sheet according to UK REACH

Version number 17 (replaces version 16)

Revision: 02.10.2024

Trade name: Mipalin

	(Contd. of page 2
· 14.3 Transport hazard class(es)	
ADR	
Class	3 (F1) Flammable liquids.
· Label	3
· IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
14.4 Packing group	
· ADR, IMDG, IATA	
<ul> <li>14.5 Environmental hazards:</li> <li>Marine pollutant:</li> </ul>	No
•	
<ul> <li>14.6 Special precautions for user</li> <li>Hazard identification number (Kemler code):</li> </ul>	Warning: Flammable liquids.
· EMS Number:	50 F-E,S-E
· Stowage Category	A
• 14.7 Maritime transport in bulk according to	
IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
Transport category	3
Tunnel restriction code	D/E
· Remarks:	≤ 450 l: 2.2.3.1.5 ADR
·IMDG	
· Limited quantities (LQ)	5L
· Remarks:	≤ 450 l: 2.3.2.5 IMDG-Code
· UN "Model Regulation":	UN 1263 PAINT, 3, III

## SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

#### Regulated poisons

None of the ingredients is listed.

(Contd. on page 9)

GB



according to UK REACH

Printing date 02.10.2024

Version number 17 (replaces version 16)

Revision: 02.10.2024

Trade name: Mipalin

(Contd. of page 8)

**Reportable explosives precursors** None of the ingredients is listed.

#### · Reportable poisons

None of the ingredients is listed.

#### · Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

• Additional classification according to Decree on Hazardous Materials, Annex II:

01	<b>Oh</b> a wa in 0/	-
Class	Snare in %	

NK

25-50

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

• Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

(Contd. on page 10)

<sup>•</sup> National regulations:



## Safety data sheet according to UK REACH

Revision: 02.10.2024

Printing date 02.10.2024

#### Version number 17 (replaces version 16)

Trade name: Mipalin

(Contd. of page 9) Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 • \* **Data compared to the previous version altered.** 

GB